

FEATURES

INTEL PC133 Version 1.0


- Clock frequency: 133MHz with CAS latency 3
- Burst read / write and burst read / single write capability
- Data input and output masking
- Programmable burst length: 1, 2, 4, 8 and full page
- Programmable burst type: sequential and interleave
- CAS latency: 3
- Auto refresh and self refresh capability
- 8K refresh per 64ms
- 256 byte serial EEPROM
- LVTTTL-compatible inputs and outputs
- Low active and standby current consumption
- Decoupling capacitors at each memory device
- Double-sided module
- 1.25 inch height
- Gold card edge fingers

DESCRIPTION

The AVD6464U39A3133E5 is Unbuffered SDRAM SODIMM memory module. This module is INTEL PC133 SDRAM SODIMM Version 1.0 compliant. A 256 byte serial EEPROM on board can be used to store module information such as timing, configuration, density, etc.

The AVD6464U39A3133E5 memory module is 512MByte and organized as a 64MX64 array using (16) 32MX8 (4 internal banks) SDRAMs in BGA packages.

All memory modules are fabricated using the latest technology design, 4 layer printed circuit board substrate construction with low ESR decoupling capacitors on-board for high reliability and low noise.



All gray ICs are on the front side of the module, and all white ICs are on the back side of the module.

BGA Package

Avant Ordering Guides

AV	D	64	64	U	39	A	3	133	E	5
INVENTORY	MOD. TYPE	ORG.	DENSITY	PARITY	TYPE	VOLT.	FEATURE	SPEED	MODE	REV
AV = AVANT	D = 144-PIN SODIMM	64=X64	64=64M	U=UNBUFFERED	39=8MX8x4 (8K)	A=3.3V	3 = CAS LATENCY 3	133MHz	E=SYNC	REV=5

Other options may be available. Call for specific part number information on options not listed.



Avant™ Technology LP., reserves the right to change products or specifications without notice.